

# SL7 GNSS Receiver

## Data Specifications

Channels	1408	1760
<b>GNSS Signal<sup>[1]</sup></b>	GPS (L1C/A, L1C, L2P(Y), L2C, L5) BDS (B1I, B2I, B3I, B1C, B2a, B2b) GLONASS (L1, L2, L3) Galileo (E1, E5a, E5b, E6) QZSS (L1, L2, L5, L6*) NavIC (L5) SBAS (L1, L2, L5) PPP (B2b-PPP, Galileo E6-HAS)	GPS (L1C/A, L2C, L2P, L5) BDS (B1I, B1C, B2a, B2b, B2I, B3I) GLONASS (L1CA, L2CA, L2P, L3) Galileo (E1, E5a, E5b, E5 AltBoc) QZSS (L1C/A, L1S, L2C, L5) NavIC (L5) SBAS* (L1, L2, L5) PPP (B2b-PPP)
<b>POSITIONING PERFORMANCE<sup>[2]</sup></b>		
<b>High-precision static GNSS Surveying</b>	H:2.5 mm + 0.1 ppm RMS / V:3.5 mm + 0.4 ppm RMS	
<b>Static and Fast Static</b>	H:2.5 mm + 0.5 ppm RMS / V:5 mm + 0.5 ppm RMS	
<b>Post Processing Kinematic (PPK / Stop &amp; Go)</b>	H:8mm + 1 ppm RMS / V:15 mm + 1 ppm RMS Initialization time: Typically 10 min for base and 5 min for rover Initialization reliability: Typically >99.9%	
<b>B2b-PPP</b>	H: 10cm / V: 20cm	
<b>Code Differential GNSS Positioning</b>	H:±0.25 m+1 ppm RMS   V:±0.5 m+1 ppm RMS SBAS: 0.5 m (H), 0.85 m (V)	
<b>Real Time Kinematic (RTK)</b>	H:8 mm+1ppm RMS / V:15 mm+1 ppm RMS Initialization time: Typically <10 s Initialization reliability: Typically > 99.9%	
<b>Time to first Fix</b>	Cold start:< 45 s   Hot start:< 30 s   Signal re-acquisition:< 2 s	
<b>Positioning rate</b>	1 Hz, 5 Hz and 10 Hz	
<b>Hi-Fix<sup>[3]</sup></b>	H: RTK+10mm / minute RMS   V: RTK+20mm / minute RMS	
<b>Tilt Survey Performance<sup>[4]</sup></b>	Additional horizontal pole-tilt uncertainty typically less than 8mm+0.7mm/°tilt(0° ~ 60°)	
<b>AR stakeout accuracy</b>	1cm	
<b>PHYSICAL</b>		
<b>Dimensions (W x H)</b>	130mm x 68mm	
<b>Weight</b>	≤ 0.75kg (1.65lb)	
<b>Operation temperature</b>	-40 C ~ +75 C (-40°F ~ +167°F)	
<b>Storage temperature</b>	-55 C ~ +85 C (-67°F ~ +185°F)	
<b>Humidity</b>	100% non-condensing	
<b>Water/dustproof</b>	IP68 dustproof, protected from temporary immersion to depth of 1.0m (3.28ft)	
<b>Shock and vibration</b>	MIL-STD-810G, 514.6	
<b>Free fall</b>	Designed to survive a 2m(6.56ft) natural fall onto concrete	
<b>ELECTRICAL</b>		
<b>Internal Battery<sup>[5]</sup></b>	Internal 7.2V / 6900mAh lithium-ion rechargeable battery RTK rover(UHF/Cellular): up to 24 hours using standard smartphone chargers or external power banks (Support 5V 2.8A Type-C USB external charging)	
<b>External power</b>		
<b>COMMUNICATION</b>		
<b>I/O Interface</b>	1 x USB type C port; 1 x SMA antenna port	
<b>WiFi</b>	Frequency 2.4GHz, Supports 802.11 b/g/n	
<b>Bluetooth</b>	BT 5.2, 2.4GHz	
<b>NFC</b>	Near Field Communication for device touch pairing	
<b>Internal UHF Radio</b>	Power: 0.5W/1W/2W Adjustable Frequency: 410MHz~470MHz Protocol: HI-TARGET, TRIMTALK450S, TRIMMARK III, SATEL-3AS, TRANSEOT, etc. Working Range: Typically 3~5km, optimal 8~15km Channel: 116 (16 scalable)	
<b>CAMERA</b>		
<b>Function</b>	Professional star-level HD camera, large viewing angle, support AR stakeout	
<b>CONTROL PANEL</b>		
<b>Physical button</b>	1	
<b>LED Lights</b>	Satellite, Signal, Power	
<b>SYSTEM CONFIGURATION</b>		
<b>Storage</b>	16GB ROM internal storage	
<b>Output format</b>	ASCII: NMEA-0183	
<b>Output rate</b>	1Hz~20Hz	
<b>Static data format</b>	GNS, Rinex	
<b>Real Time Kinematic (RTK)</b>	RTCM3.X	
<b>Network Mode</b>	VRS, FKP, MAC, Support NTRIP protocol	



Headquarters:  
GEOSOLUTION | GÖTEBORG AB  
Stora Ävägen 21, 436 34  
ASKIM, Sweden  
Regional Offices:  
Budapest, Hungary  
Ankara, Turkey  
Dubai, UAE  
New Delhi, India  
Scottsdale, USA  
Tokyo, Japan  
Hong Kong, China

[www.satlab.com.se](http://www.satlab.com.se)



AUTHORIZED DISTRIBUTION PARTNER

Note:  
[1] SBAS service can be provided by firmware upgrade, PPP service is not available in all regions, check with your local sales representative for more information.  
[2] The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.  
[3] Accuracies are dependent on GNSS satellite availability. Hi-Fix Positioning ends after 5 minutes without differential data.  
[4] Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.  
[5] The battery operating time is related to the operating environment, operating temperature and battery life  
Descriptions and Specifications are subject to change without notice



# SL7 GNSS Receiver



### Powerful Satellite Tracking and Anti-jamming Capabilities

SatLab's unique design and self-developed antenna promise a stable and efficient operation. A highly integrated motherboard chip with low power consumption, supporting up to 1760 channels, tracks full constellations and frequencies. The excellent hardware configuration suppresses signal interference and obtains high-quality satellite-tracking data, ensuring performance and accuracy even in complex environments.



### Visual Navigation Makes Stakeout Easier

Star-level HD camera provides users with immersive 3D visual navigation and stakeout experience. The featured AR stakeout on the Satsurv software provides guidance of the pointing arrow on the real scene and the real-time distance display to users for quickly locating the target point. And the AR function can also be performed in activities such as line stakeout and CAD-based map stakeout. The AR stakeout improves working efficiency by nearly 50% compared with the traditional graphics and text mode stakeout.

### Accurate and Reliable Tilt Measurement

The SL7 utilizes SatLab's most advanced tilt measurement technology, and with built-in 200Hz IMU module and automatic initialization upon turning on can automatically complete the tilt calibration process without waiting for a fixed solution during operation. And it can measure and stakeout with survey-grade accuracy within a tilt compensation range of up to 60°, increasing efficiency by nearly 30%.



### Longer Battery Life and Better Portability

Optimized the whole structure with new hardware, the nimble GNSS smart antenna weighs only 750g, Its energy-efficient hardware design ensures an extended operational battery life of up to 24 hours, allowing users to enjoy portability without worrying about battery drain.

### Key Features



### Applications

- Monitoring
- Land Survey
- Mapping
- Hydrographic
- Topography and As-built
- Agriculture

